

ES1932

Electric Scissor Lift



Performance

Platform Height – Elevated (Indoor/Outdoor)	5.8/5.8 m
Platform Capacity (Indoor/Outdoor)	230/230 kg
Platform Capacity (Deck Extension)	120 kg
No. Occupants (Indoor/Outdoor)	2/1
Lift/Lower Time	36/28 sec
Maximum Drive Height	Full Height
Ground Bearing Pressure	8.2kg/cm ²
Weight	1,565 kg
Drive Speed – Elevated	0.8 km/h
Drive Speed – Lowered	4.8 km/h
Gradeability	25%
Tilt Rating Side to Side (Indoor/Outdoor)	1.75°/1.5°
Turning Radius (Inside/Outside)	0 m/1.7 m

Standard Specifications

Power Source

Batteries	4 x 6V 220 amp-hr
Charger	27 amp
Drive	24V DC

Hydraulic Reservoir

Capacity	7L
Pump	Fixed Displacement Gear

Tires

Tire Size/Type (Non-Marking) 323 x 100mm

Standard Features

- Proportional Controls
- Battery Condition Indicator
- AC Receptacle in Platform
- All Motion Alarm
- 27 amp Multi-Function Universal Charger
- Horn
- Hourmeter
- Tilt Alarm and Light
- Lanyard Attachment Points
- Movable, Removable Control Box
- Nickel Plated Pins
- Lubrication Free Scissor Arm Bushings
- Removable Ladder
- QuikFold Rails
- Smart Charger
- USB Charger & Phone Holster
- Scissor Maintenance Prop
- Active Pothole Protection System
- Lifting and Tie Down Points
- Fork Lift Pockets
- Foot-Actuated Deck Extension
- Steel Swing Out Doors
- Variable Tilt Visual Zone Indicator
- Manual Decent Cable
- Diamond Trend Steel Deck
- Greaseless Kingpin Joints
- Analyzer Port for Diagnostics
- Dynamatic Braking
- Self-Closing Gate
- DC Electric Drive
- Telematics-Ready Harness
- Load Sensing System
- ANSI A92.20 Compliant

Accessories & Options

- CleanGuard
- Coiled Platform Control Box Cable
- Drive Motor Covers
- Flashing Amber Beacon
- MDI (Ground)
- Anti-Vandalism PKG
- Eagle Performance Charger
- 900W Inverter
- White Noise Alarm
- JLG™ Mobile Control
- SkySense™ Level I
- QuickAccess Platform



Dimensions

All dimensions are approximate.



Platform Height – Elevated	5.8m
A. Platform Height – Lowered	1.0m
B. Platform Railing Height	1.1m
C. Overall Height	1.63m
D. Platform Dimensions	1.59 x 0.64m
E. Platform Extension	0.91m
F. Overall Machine Length	0.81m
G. Overall Machine Width	1.7m
H. Wheelbase	1.3m
I. Ground Clearance	7cm

The JLG “1 & 5” Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.