

ELECTRIC SERIES SCISSOR LIFTS

# 0608SE(1930SE)/0608ME(1932ME)

Compliance with ISO/CE/ANSI/CSA/AS/EAC standards

## PRODUCT HIGHLIGHTS

### Efficient and environmentally friendly

- Higher work efficiency
- Environmental protection, zero emissions

### Reduced maintenance costs

- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts

### Reliable performance

- Bumper rail protection



#### Standard features

|                          |   |                                  |
|--------------------------|---|----------------------------------|
| Maintenance-free battery | Automatic braking system                            | Drive at full height             |
| Proportional control     | Emergency lowering system                           | Forklift pocket and lifting eyes |
| Bumper rail              | Emergency stop at both platform and ground controls | Electrophoresic paint technology |
| 2WSx2WD                  | Fault diagnosis system                              | Foldable guardrail               |
| Non-marking tyres        | Tilt protection                                     | Overload sensing system          |
| Integrated hand shield   | Automatic pothole guard                             |                                  |

#### Optional features

|                                |             |      |
|--------------------------------|-------------|------|
| Overhead anti-collision device | Headlight   | RCBO |
| AC power to platform           | Foot switch |      |

**SINOBOOM™**

**PARTNERS IN ACCESS™**

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ELECTRIC SERIES SCISSOR LIFTS

# 0608SE(1930SE)/0608ME(1932ME)

Compliance with ISO/CE/ANSI/CSA/AS/EAC standards

| Model  | 0608SE/0608ME(1930SE/1932ME)                  |
|--|---|
| <b>Dimensions</b>                            |   |
| Max Working Height                           | 7.8m(25'7")                                   |
| A Max Platform Height                        | 5.8m(19')                                     |
| B Max Horizontal Extension                   | 0.9m(3')                                      |
| C Length-Stowed                              | 1.8m(5'11")                                   |
| D Width-Stowed                               | 0608SE 0.79m(2'7") / 0608ME 0.81m(2'8")       |
| E Height-stowed (Rail Folded)                | 1.88m(6'2")                                   |
| E Height-stowed (Rail Unfolded)              | 2.14m(7')                                     |
| F Wheelbase                                  | 1.33m(4'4")                                   |
| Ground Clearance(Pothole Guard Stowed)       | 75mm(3")                                      |
| Ground Clearance(Pothole Guard Deployed)     | 24mm(0.95")                                   |
| Platform Dimensions(LxWxH)                   | 1.64m x 0.76m x 1.1m(5'5" x 2'6" x 3'7")      |
| <b>Performance</b>                           |   |
| Platform Allowable Occupants(Indoor/Outdoor) | 0608SE(2persons/-), 0608ME(2persons/1 person) |
| Platform Capacity                            | 230kg(507lbs)                                 |
| Drive Speed-Stowed                           | 4km/h(2.5mph)                                 |
| Drive Speed-Raised                           | 0.8km/h(0.5mph)                               |
| Elevation Time(Unloaded)                     | 15s~20s                                       |
| Descent Time(Unloaded)                       | 25s~30s                                       |
| Gradeability                                 | 25%   |
| Turning Radius(Inside/Outside)               | 0/1.49m(0/4'11")                              |
| Tilt Rating(Front to Back/Side to Side)      | 3°/1.5°                                       |
| Tyre Size/Type                               | 323x100mm(12.7x4")/solid                      |
| <b>Power</b>                                 |   |
| Batteries                                    | 6Vx4/225Ah                                    |
| Power Source                                 | 24V DC  |
| Drive Mode                                   | Motor, front-wheel                            |
| Charger Input                                | 100~240V AC                                   |
| Charger Output                               | 30A   |
| Hydraulic Tank Capacity                      | 7L(1.54gal(UK)/ 1.85gal(US))                  |
| <b>Weight</b>                                |   |
| Weight                                       | 1,575kg(3,473lbs)                             |
| Standards Compliance                         | ISO/CE/ANSI/CSA/AS/EAC                        |

