



KUBOTA L5740 HST TRACTOR BROOM COMBO



The 59 HP L5740 HST tractor & **NEILO** Broom Combo delivers the ultimate in operator comfort, brooming performance and reliability for those demanding front line crews where productivity and speed is a factor.

The L5740 Broom Combo is available in both air conditioned factory cabin and ROPS platform types.

The Servo operated HST "PLUS" Transmission features advantages such as a 2 speed power shift function, step-less lever type cruise control and load sensing auto throttle.

The L5740 cabin or ROPS Combo can be transported on a (gross weight 3500kg) tandem trailer behind a utility vehicle with a 3000 to 3500kg towing capacity such as the new Ford Ranger

We have combined the proven performance and reliability of the Kubota L Series with **NEILO's** unique broom technology to create the ultimate sweeper.

Choose between our 5 section 1.75m or 6 section 2.1m brooms, the L5740 has the power to handle both.

Our brooms unique spring loaded contour following lateral pivot substantially reduces brush wear and coning. Brush sections can be changed in the field in just minutes.

The *Kubota* Tractor & **NEILO** Broom Combo is ready for work as soon as you receive it complete with flashing light and remote mounted "Top Spin" pre cleaner, because "**at NEILO we like to make it easy**"



FEATURE OVERVIEW

- 59hp engine with 3 range HST “PLUS” Hydrostatic transmission
- Air conditioned & heated factory cabin with CD player: cab model
- Remote mounted Top spin pre cleaner on cabin or ROPS
- Front mounted 5 section 1.75m or 2.1m 6 section Broom head
- Pivoting type hydraulic lift & hydraulic left right hydraulic angle
- Convenient hydraulic joy stick to control broom lift and angle
- Broom drive via independent PTO driven hydraulic pump
- Convenient Clutch-less engagement of broom drive
- Filtered rear mounted 70 litre hyd. reservoir for maximum cooling
- Operator can easily replace brush sections in the field
- Unique spring activated contour following lateral pivot ensures even brush pressure & reduced coning



KUBOTA TRACTOR SPECIFICATION

Diesel Engine	4 cylinder, 2434cc, Turbocharged
HP	59HP (44.0kw) @2700rpm
Transmission	Servo operated 3 range HST Hydrostatic with dual speed power shift
Trans cont.	Step-less lever type cruise control & load sensing auto throttle
Fuel Capacity	44 litres
PTO	Clutch-less hydraulic independent type
Air Filtration	Dual type filters with remote “Top Spin” pre cleaner
Total Hydraulic Flow	50.1 lpm
Steering	Hydrostatic power steering
Tyres	Front 212/80-D15 rear 355/80-D20 Turf / Tarmac type

NEILO BROOM SPECIFICATION

Broom Width Overall	2.130 metres (optional 6 brush 2.480 metres)	
Sweeping Width (max)	1.750 metres (optional 6 brush 2.100 metres)	
Sweeping Width (angle min)	1.660 metres (info not available)	
Broom Diameter	530mm	
Number of Brush Sections	Std. 5 x 350mm optional 6 x 350	
Broom Speed	150 RPM	
Angles left and Right	Variable to 60° left 60° right	
Drive	Hydraulic Via a pump & 3 to 1 step up box on rear PTO	
Oil Tank Capacity	70 litre tank mounted at rear of tractor	
Contour Following Pivot	Unique Spring Loaded Contour Following Pivot reduces brush wear and coning	
Filtration	Return line filter in tank	
Broom Lift	Joystick controlled SA valve with float function	
Angle	Joystick controlled DA valve	
Length ROPS/Cabin Combo	With broom straight 4.4m	
Weight Tractor/ Broom	L5740 ROPS 2070kg est.	L5740 Cabin 2220 kg
Replacement of Brushes	Remove two nuts. Pull off left hand end cap. Replace brush sections on shaft. Replace end cap and bolt.	
Brush Manufacturer	NZ Brush Co.	
Country of Manufacture	Tractor Japan, Broom & Brush sections New Zealand	

Neil O'Fee Equipment reserves the right to change the above specification without notice
We strongly recommend the use of seat belts in almost all applications.



Kubota Tractor Grader and Broom Combos distributed by
NEIL O'FEE EQUIPMENT LTD
 Mobile 027 6642211
 Office: (06) 3551139 Fax (06) 3551432
 Email neilofee.equipment@xtra.co.nz
 Web site: www.neilo.co.nz

