

BX80 Series Specifications

Model			BX1880	BX2380	BX2680	BX23S
Engine	Type		Liquid-cooled, 3-cylinder diesel			
	Model		Kubota D722	Kubota D902	Kubota D1005	Kubota D902
	Engine gross HP at 3200 rpm*	HP (kW)	18.0 (13.4)	23.0 (17.1)	25.5 (19.0)	23.0 (17.1)
	PTO horsepower at 3200 rpm	HP (kW)	13.7 (10.2)	17.7 (13.2)	19.5 (14.5)	17.7 (13.2)
	Displacement	cu.in. (cc)	43.9 (719)	54.8 (898)	61.1 (1001)	54.8 (898)
	Fuel tank capacity	/	25			
Drive train	Transmission		HST, High-Low gear shift (2 forward / reverse)			
	Drive method		4WD			
	Brakes		Wet disc			
	PTO		Live independent PTO (with hydraulic clutch)			
	PTO - Rear		STD (540rpm)			
	PTO - Mid		STD (2500rpm)			
Hydraulics	Pump output	l/min	23.5			
	3-point hitch		SAE Category I			Optional

Model			BX1880	BX2380	BX2680	BX23S
	Lift capacity @ 24" behind pin	kg	310			
	Steering		Hydrostatic Power Steering			
Tyre size	Front	Turf/Bar/Industrial	16×7.5–8 / 16×7.5–8 / N.A.	18×8.5–10 / 18×8.5–10 / 18×8.5–10		
	Rear	Turf/Bar/Industrial	24×12–12 / 24×12–12 / N.A.	26×12–12 / 26×12–12 / 26×12–12		
Travelling speeds at rated engine rpm (Turf)	Forward	km/h	0–12.5	0–13.5		
	Reverse	km/h	0–9.5	0–10.5		
Dimensions	Length with 3-point hitch	mm	2425			2515 w/ Front guard
	Width	mm	1120	1145		
	Height with ROPS	mm	2080	2110		2190
	Wheelbase	mm	1400			
	Ground clearance (front axle)	mm	193	213		
	Tread Front	mm	930			
	Tread Rear	mm	820			
	Turning radius (w/o brake)	m	2.3			

Model			BX1880	BX2380	BX2680	BX23S
	Tractor weight (w/ROPS)	kg	606	650	670	712 *2

f (<https://www.facebook.com/kubotanz>) 

[Terms of Use \(https://www.kubota.co.nz/terms-of-use/\)](https://www.kubota.co.nz/terms-of-use/)

[Privacy Policy \(https://www.kubota.co.nz/credit-reporting-policy-2/\)](https://www.kubota.co.nz/credit-reporting-policy-2/)

[Site Map \(https://www.kubota.co.nz/site-map/\)](https://www.kubota.co.nz/site-map/)

Kubota New Zealand

Copyright © 2020 Kubota New Zealand. All Rights Reserved