

Kubota



KUBOTA DIESEL TRACTOR

L3240/L3540/L4240 L5240/L5740

The deluxe diesel tractor designed and built to meet your needs.



Note: This information is sourced from overseas and may not necessarily apply locally. It is essential that you confirm specifications and other information with your local Kubota dealer.

Note: Pictured loaders are non mechanical self levelling U S A models. Loaders available from Kubota Tractor Australia are mechanical self levelling models only.

Life is
Grand
The Kubota Grand L40 Series

SPECIFICATIONS

Model	L3240				L3540			
	DT (4WD)		HST (4WD)		HST (4WD)		HST (4WD)	
Engine Type	E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel				E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel			
Engine gross power	HP (kW)	34.0 (25.4)		37.0 (27.6)				
Engine net power	HP (kW)	32.0 (23.9)		35.0 (26.1)				
PTO power	HP (kW)	26.5 (19.8)	25.0 (18.7)	28.0 (20.9)	35.0 (26.1)			
No. of cylinders / Aspiration	3 / Natural		3 / Natural		3 / Natural			
Bore & stroke	mm	87 × 92.4		87 × 102.4				
Total displacement	cc	1647		1826				
Rated speed	rpm	2700		2700				
Battery	12V, RC: 123 min, CCA: 490A				12V, RC: 133 min, CCA: 582A			
Alternater	12V, 40A				12V, 40A			
Fuel tank capacity	ℓ	44		44				
PTO Rear PTO Revolution	1 speed: 540 rpm				1 speed: 540 rpm			
Type	Independent		Independent**		Independent**		Independent	
Mid PTO Revolution	Option 1 speed: 2000 rpm				Option 1 speed: 2000 rpm			
Hydraulic Lift control type: Position Draft	Standard Option				Standard Option			
Implement pump	ℓ/min.	31.5		31.5				
Power steering pump	ℓ/min.	18.6		18.6				
Total hydraulic flow	ℓ/min.	50.1		50.1				
3-point hitch	Category I				Category I			
Lift capacity at 24 in. behind lift point	kg	1200		1200				
Travelling System Transmission	FST 8F/8R		HST Plus (3 Ranges)		HST Plus (3 Ranges)			
Steering	Hydrostatic power steering				Hydrostatic power steering			
Brake	Wet disc type				Wet disc type			
Clutch	Dry type single stage				Dry type single stage			
Standard tyre size**	Front	7.0-16		7.0-16				
	Rear	12.4-24		12.4-24				
Travel speeds No. of speeds (at rated engine speed)	km/h	FST		HST Plus				
		Forward	Reverse		Forward	Reverse	Forward	
	Low	1: 1.6	1.5	H-DS L	L: 3.5	L: 3.1	H-DS L	
		2: 2.3	2.2		M: 7.1	M: 6.4	L: 3.6	
		3: 3.7	3.5		H: 15.0	H: 13.5	M: 7.3	
		4: 5.3	5.1				H: 15.5	
	Hi	1: 7.7	7.4	H-DS H	L: 5.8	L: 5.2	H-DS H	
		2: 11.0	10.5		M: 11.8	M: 10.6	L: 6.0	
		3: 17.8	17.0		H: 25.0	H: 22.5	M: 12.3	
		4: 26.3	25.1				H: 26.0	
Dimensions Overall length (w/o 3P)	mm	2960		2960				
Overall width (min. tread)	mm	1520		1520				
Overall height (w/Foldable ROPS)	mm	2385		2385		2405		
Wheelbase	mm	1805		1805				
Min. ground clearance	mm	350		350				
Tread	Front (Front tire)	1150		1150				
	Rear (Rear tire)	1200 1300 1385 1480		1200 1300 1385 1480				
Min. turning radius (w/brake, 4WD disengaged)	m	2.7		2.7				
Weight (with ROPS)	kg	1475		1540		1665		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

**With Master Clutch.

**Kubota offers several tire options.